Material Safety Data Sheet

May be used to comply with OSHA'S Hazard Communication Standard 29 CFR 2910.1200. Standard must be consulted for specific requirements.

U.S. DEPARTMENT OF LABOR

Occupational Safety and Health (Non-Mandatory Form) Form Approved OMB No. 1218-0072

Identity (As Used on Label and List) #334, #416 Big D Liquid Deodorant , Apple	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.			
Section I				
Manufacturer's Name Big D Industries, Inc.	Emergency Telephone Number (800) 535-5053 (800) 654-4752			
Address (number, Street, City, State, and ZIP Code) 5620 S. W. 29th Street (73179)	Telephone Number for Information (800) 654-4752 (405) 682-2541			
P. O. Box 82219	Date Prepared 01/01/1999			
Oklahoma City, OK 73148	Signature of Preparer (optional)			

Section II - HMIS Rating							
Health	1	Flammability	2	Reactivity	0		

Section III - Hazardous Ingredients/Identity Information					
Hazardous Components (Specific Chemical Identity: Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits		
%(optional)					
			Remnd.		
Amyl Acetate CAS #628-63-7	100 ppm	100 ppm	-		
DiPropylene Glycol methyl ether CAS #20324-32-7	100 ppm	150 ppm	-		
Ethyl Acetate CAS #141-78-6	400 ppm	400 ppm			
Propylene Glycol CAS #57-55-6	N/E	N/E	•		
Benzyl Alcohol CAS #100-51-6	N/E	N/E			

Section IV - Physical/Chemical Characteristics				
Boiling Point	N/D	Specific Gravity (H ₂ O = 1)	N/D	
Vapor Pressure (mm Hg.)	N/D	Melting Point	N/A	
Vapor Density (AIR = 1)	>1	Evaporation Rate	<1	

Solubility in Water:	Slight
Appearance and Odor:	Clear liquid with Apple fragrance

Section V - Fire and Explosion Hazard Data						
Flash Point (Method Used) N/D	Flammable Limits N/A	LEL	UEL			
		N/A	N/A			
Extinguishing Media Carbon dioxide or dry foam						
Special Fire Fighting Procedures None						
Unusual Fire and Explosion Hazards None						

1100 1 110				
Section VI - Reactivity Data				
Stability	Unstable		Conditions to Avoid: None	
	Stable	X		
Incompatibility (Ma	aterials to Avoid): Av	oid contac	et with strong oxidizing agents such as nitric acid.	
Hazardous Decomp	osition or Byproducts:	None		
Hazardous Polymerization	May Occur		Conditions to Avoid: None	
	Will Not Occur	X		

Section VII - Health Hazard Data
Route(s) of Entry: Inhalation? Yes Skin? Yes Ingestion? Yes
Health Hazards (Acute and Chronic): Acute - Oral LD50 (Rats) = 10.3 grams/kilogram body weight. Chronic - Low order of toxicity. Frequent
or prolonged contact may irritate skin. Inhalation - Non hazardous under short term conditions.
Carcinogenicity: NTP? No IARC Monographs? No OSHA Regulated? No
Signs and Symptoms of Exposure: None known
Medical Conditions None known
Generally Aggravated by Exposure: None Known
Emergency and First Aid Procedures: Eye contact: flush with large amounts of water. May cause corneal damage on prolonged contact. Seek
medical attn.
Ingestion: Do not give anything by mouth to an unconscious person. Seek Medical attn. Inhalation: remove person to fresh air . Seek
medical attn.

Section VIII - Precautions for Safe Handling and Use				
Steps to be Taken in Case Material is Released or Spilled: Wash small spills with soap and water. For large spills soak up with inert absorbent material.				
Waste Disposal Method: Landfill for absorbent material. Do not incinerate. Dispose of in accordance with Local, State, and Federal				
regulations.				
Precautions to be Taken in Handling and Storing: Do not store near heat nor open flame				
Other precautions: None				

Section IX - Control Measures				
Respiratory Protection (Specify Type): None required				
Ventilation	Local Exhaust adequate	Special N/A		
	Mechanical (General) adequate	Other N/A		
Protective Gloves: Rubber or plastic for prolonged contact Eye Protection: Safety goggles for splash protection				
Other Protective Clothing or Equipment: Eye wash/shower facility nearby				
Work/Hygienic Practices: Good housekeeping practic	es. Avoid skin/eye contact.			

N/A = Not Applicable N/D = Not Determined Page 2 N/E = Not Established OSHA 174, Sept. 1985