MATERIAL SAFETY DATA SHEET

HARRISON PAINT COMPANY EXCELSIOR COATINGS DIV 1329 HARRISON AVE SW CANTON, OH 44706

EMERGENCY PHONE: 330/455-5125 PREPARATION DATE: 6/8/06 REPLACES DATE: 12/9/02

SECTION I - PRODUCT IDENTIFICATION

Waterless Cleaner - 2702

SECTION II - HAZARDOUS INGREDIENTS

CHEMICAL NAME	CAS NUMBER	WT. % IS LESS THAN	(TLV-TWA)	OCCUPATIONAL EXPOSURE LIMITS (TLV-STEL)	(PEL)	VAPOR PRESSURE MgHg 20C	KNOWN OR SUSPECTED CARCINOGEN	SEC 313
AROMATIC PETROLEUM DISTILLATES	64742-95-6	5.0%	NO INFO	NO INFO	NO INFO	0.0	NO	NO
TRIMETHYLBENZENES	25551-13-7	10.0%	25 PPM	NO INFO	NO INFO	0.0	NO	YES
HYDROTREATED DISTILLATE, LIGHT	64742-47-8	80.0%	100 PPM	NO INFO	100 PPM	1.0	NO	NO

THIS PRODUCT CONTAINS ONE OR MORE MATERIALS SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING AND THE COMMUNITY RIGHT-TO-KNOW ACTS OF 1986 AND OF 40 CFR 372.

Boiling Range: Odor: Appearance: Volatile by Weight: Volatile by Volume:

SECTION III - PHYSICAL DATA

367-405 F Petroleum Solvent Clear, Colorless 100.0% 100.0% Vapor Density: Evaporation Rate: Solubility: Product Density: Is heavier than air Is slower than ether None 6.6 lbs./gal. (U.S.)

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flammability Classification:	FLASH POINT: 140 F.	LEL: 1.0	1%
OSHA – COMBUSTIBLE LIQUID – CLASS IIIA	(CLEVELAND OPEN CUP)	UEL: 7.0	1%
DOT - COMBUSTIBLE LIQUID			

Extinguishing Media: DRY CHEMICAL CARBON DIOXIDE FOAM

UNUSUAL FIRE AND EXPLOSION HAZARDS: WATER MAY BE USED TO COOL CLOSED CONTAINERS NOT INVOLVED IN THE FIRE ITSELF. TO PREVENT PRESSURE BUILD-UP AND POSSIBLE AUTOIGNITION OR EXPLOSION WHEN EXPOSED TO EXTREME HEAT. SPECIAL FIRE FIGHTING PROCEDURES: FIRE FIGHTERS SHOULD WEAR NIOSH/OSHA APPROVED PRESSURE DEMAND, SELF CONTAINED BREATHING APPARATUS.

SECTION V - HEALTH HAZARD DATA

EFFECTS OF OVER EXPOSURE: EYES: IRRITANT, DISCOMFORT, BLURRED VISION, BURNING. SKIN: PROLONGED OR REPEATED SKIN CONTACT MAY RESULT IN IRRITATION, SENSITIZATION AND DERMITITIS. INGESTION: MAY CAUSE NAUSEA AND VOMITING. INHALATION FO FUMES MAY RESULT IN DIZZINESS, HEADACHE, BLURRED VISION OR UNCONSCIOUSNESS. MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE: PRE-EXISTING SENSITIVITY TO SOLVENTS CAN CAUSE A HEIGHTENED REACTION BY EXPOSURE TO THIS PRODUCT.

PRIMARY ROUTE(S) OF ENTRY: DERMAL INGESTION INHALATION

EMERGENCY AND FIRST AID PROCEDURES: SKIN: WASG THOROUGHLY WITH SOAP AND WATER. EYES FLUSH WITH LARGE AMOUNTS OF COOL WATER FOR AT LEAST 15 MINUTES. CONSULT A PHYSICIAN. INHALATION: REMOVE VICTIM TO FRESH AIR AND ADMINISTER OXYGEN IF

SECTION VI - REACTIVITY DATA

STABILITY: HAZARDOUS POLYMERIZATION:	THIS PRODUCT IS STABLE UNDER NORMAL STORAGE CONDITIONS. WILL NOT OCCUR UNDER NORMAL CONDITIONS.
HAZARDOUS DECOMPOSITION PRODUCTS:	COMBUSTION MAY YIELD CARBON MONOXIDE AND/OR CARBON DIOXIDE.
CONDITIONS TO AVOID:	DO NOT STORE OR USE NEAR OPEN FLAMES OR IN AREAS OF HIGH
INCOMPATABILITY:	STRONG OXIDANTS, ALKALIS.

SECTION VII - SPILL OR LEAKAGE PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: NOTIFY LOCAL FIRE DEPARTMENT AS A SAFETY PRECAUSTION. AVOID BREATHING VAPOR, ENSURE ADEQUATE VENTILATION. USE SAND OR OTHER INERT MATERIAL TO DAM AND CONTAIN SPILL. DO NOT FLUSH AREA WITH WATER. WASTE DISPOSAL METHOD: CHECK COMPANY'S POLICY ON DISPOSAL. DISPOSAL SHOULD BE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

SECTION VIII - SAFE HANDLING AND USE INFORMATION

RESPIRATOR PROTECTION: NIOSH/OSHA APPROVED RESPIRATOR TYPES, SUITABLE FOR MATERIALS IN SECTION II RECOMMENDED. APPROVED CHEMICAL/MECHANICAL FILTERS RECOMMENDED WHEN VENTILATION IS RESTRICTED.

VENTILATION: SUFFICIENT VENTILATION IN VOLUME AND PATTERN SHOULD BE PROVIDED TO KEEP AIR CONTAMINATION BELOW CURRENT APPLICABLE OSHA PERMISSIBLE EXPOSURE LIMITS OR ACGHI'S TLV LIMIT.

PROTECTIVE GLOVES: USE IMPERMEABLE GLOVES. EYE PROTECTION: CHEMICAL GOGGLES WITH SIDE SHIELDS OR FACE SHIELD RECOMMENDED. OTHER PROTECTIVE EQUIPMENT: EYEWASH STATION/SAFETY SHOWER. IMPERVIOUS BOOTS AND APRON TO MINIMIZE SKIN CONTACT. HYGIENIC PRACTICES: REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE. WASH HANDS BEFORE AND AFTER USE.

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: STORE IN CLEAN DRY AREA IN PROPERLY LABELED CONTAINERS. READ COMPLETE DIRECTIONS AND PRECAUTIONS BEFORE USE. NO SMOKING SIGNS SHOULD BE POSTED AND ENFORCED. KEEP CONTAINERS CLOSED WHEN NOT IN USE. STORE AWAY FROM EXCESSIVE HEAT.

OTHER PRECAUTIONS: ALL CONTAINERS SHOULD BE DISPOSED OF IN AN ENVIRONMENTALLY SAFE MANNER OR RETURNED TO A DRUM RECONDITIONER.

SECTION X - HMIS RATINGS

HEALTH: 2 FLAMMABILITY: 2 REACTIVITY: 0

SECTION XI - STATE REGULATIONS

CALIFORNIA PROPOSITION 65: **WARNING:** THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS, OR OTHER REPRODUCTIVE HARM.

THE INFORMATION CONTAINED HEREIN IS, TO THE BEST OF OUR KNOWLEDGE AND BELIEF, ACCURATE. HOWEVER, SINCE THE CONDITIONS OF HANDLING AND USE ARE BEYOND OUR CONTROL, WE MAKE NO GUARANTEE OF RESULTS, AND ASSUME NO LIABILITY FOR DAMAGES INCURRED BY USE OF THIS MATERIAL. IT IS THE

RESPONSIBILITY OF THE USER TO COMPLY WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS.